


PRODUCT:

GRECAPIU'

5 Ribs 80/20

SHEET SECTION



TECHNICAL SPECIFICATIONS:

DATA	UNIT	SPECIFICATIONS
Thickness	mm	20 ±5%
Sheet pitch	mm	1000 ±5
Rib pitch	mm	250
Rib height	mm	82 central 80 side
Sheet length	m	To measure (max recommended length: 7.00 m)
Bending	(R) m	Standard hot bending R 3.5 or 6 <i>Variable radii are available on request</i> <i>Contact the Technical Department</i>
Compliant with the reference standard	-	UNI EN 16153:A1:2015
Colour	-	Satined clear and Opal
Structure	-	Honeycomb
U.V. protection	-	UV-protected on the external side
Fire Classification	-	B s1 d0
Operating temperature	°C	-40° / + 130°
Linear Thermal Expansion	mm/mm °C	6.7 x10 ⁻⁵
Resistance to chemical agents and use and maintenance	-	Refer to the catalogue for the specifications
Thermal Transmittance	W/m ² K	U= 1.80
Light transmission	%	Clear 62 ±2 Opal 43 ±2
Warranty	-	10 years - Refer to our Warranty for the terms and conditions

SIDE RIBS:

STANDARD WIDTHS

Special treatments



U.V. protection



Bi-colouring




Matt treatment



IR treatment

For information on resistance to chemical agents, frame the QR Code:


POLYPIU







LOAD TABLES:

FLAT APPLICATION



CURVED APPLICATION



For CURVED GRECAPIU' with a radius of 3.5 and 6 m in multiple applications (2), with a span of more than 3 m and purlin centres ranging from 3.0 to 3.75 m, combination with sheet with a high calendered square upright

Special treatments



U.V. protection



Bi-colouring



Matt treatment



IR treatment

For information on resistance to chemical agents, frame the QR Code:

POLYPIU

