


PRODUCT: _____
SHEET SECTION


PANELPIU' 500/20 **20 mm Honeycomb**



TECHNICAL SPECIFICATIONS:

DATA	UNIT	SPECIFICATIONS
Thickness	mm	20 ±5%
Structure	-	Honeycomb
Sheet width	mm	500 ±5
Sheet length	m	Made to measure
Closure at the ends	-	Sealing with aluminium tape
Compliant with the reference standard	-	UNI EN 16153:2015
Colour	-	Satined clear – Opal (other colours are available on request)
U.V. protection	-	UV-protected on the external side
Fire Classification	-	B s1 d0
Operating temperature	°C	-40° / + 130°
Linear Thermal Expansion	mm/mm °C	6.7 x10 ⁻⁵
Resistance to chemical agents and use and maintenance	-	Refer to the catalogue for the specifications
Thermal Transmittance	W/m ² K	1.82
Light Transmission	- CLEAR	64±2
	- OPAL	41±2
Solar factor	- CLEAR	75±2
	- OPAL	50±2
Warranty	-	10 years - Refer to our Warranty for the terms and conditions

LOAD TABLES:



Special treatments



U.V. protection



Bi-colouring



Matt treatment



IR treatment

For information on resistance to chemical agents, frame the QR Code:

POLYPIU

