

PANEL PIU'

Flat False ceiling

PANELPIU'
PA 600/10

07.10.2025

POLYPIU' SRL
Via A. da Giussano, 15
20011 Corbetta (MI), Italy


Telephone +39 02 9748371
polypiuinfo@polypiu.it

PRODUCT:

PANELPIU' 600/10

10 mm FOR FALSE CEILING

SHEET SECTION



TECHNICAL SPECIFICATIONS:

DATA	UNIT	SPECIFICATIONS
Thickness	mm	10 ±5%
Structure	-	Three walls
Sheet width	mm	600 ±5
Sheet length	m	Made to measure
Closure at the ends	-	Sealing with aluminium tape
Compliant with the reference standard	-	UNI EN 16153:2015
Colour	-	Satined clear – Opal
U.V. protection	-	Normal - NOT UV-PROTECTED
Fire Classification	-	B s1 d0
Operating temperature	°C	-40° / + 130°
Linear Thermal Expansion	mm/mm °C	6.7×10^{-5}
Resistance to chemical agents and use and maintenance	-	Refer to the catalogue for the specifications
Thermal Transmittance	W/m²K	2.70
Light Transmission	%	79±2
	%	64±2
Warranty	-	10 years - Refer to our Warranty for the terms and conditions

APPLICATION:

APPLICATION TO INTERIOR FALSE CEILING	MAXIMUM SPAN: 1.50 m on two supports - Sheet restrained at the ends
--	--

Special treatments



U.V. protection



Bi-colouring



Matt treatment



IR treatment

For information on resistance to chemical agents, frame the QR Code:

POLYPIU'



LIABILITY CLAUSE: all information and technical guidance provided is given in good faith and according to the best of our knowledge. However, as we have no control over how our materials are used, we accept no responsibility for their application. The instructions do not exempt the purchaser from carrying out their own checks to ensure that the materials comply with their own needs and the current regulations. Polypiu S.r.l. reserves the right to modify its products and the content of its documentation at any time without prior notice.