


PRODUCT:

SMARTPIU'

Greca 21/78

## SHEET SECTION



### TECHNICAL SPECIFICATIONS:

DATA	UNIT	SPECIFICATIONS
Thickness	mm	2.5 ±5%
Useful sheet pitch	mm	936±5
Sheet width	mm	1020±5
Rib pitch	mm	78
Rib height	mm	21
Sheet length	m	To measure (max recommended length: 7.00 m)
Compliant with the reference standard	-	UNI EN 16153:A1:2015
Bending	(R) m	Standard hot bending R 3.5 or 6 <i>Variable radii are available on request</i> <i>Contact the Technical Department</i>
Colour	-	Satined clear – Opal
Structure	-	Single-chamber
Closure at the ends	-	Cell heat-sealing
U.V. protection	-	UV-protected on the external side
Fire Classification	-	B s1 d0
Operating temperature	°C	-40° / + 130°
Linear Thermal Expansion	mm/mm °C	6.7 x10 <sup>-5</sup>
Resistance to chemical agents and use and maintenance	-	Refer to the catalogue for the specifications
Thermal Transmittance	W/m <sup>2</sup> K	U= 4.71
Light transmission	%	Clear 83 ±2      Opal 72 ±2
Warranty	-	10 years - Refer to our Warranty for the terms and conditions

### Special treatments



U.V. protection



Bi-colouring




Matt treatment



IR treatment

### For information on resistance to chemical agents, frame the QR Code:

# POLYPIU



**POLYPIU' SRL**


Via A. da Giussano, 15  
20011 Corbetta (MI), Italy

Telephone +39 02

9748371

polypiuinfo@polypiu.it

LOAD TABLES:



Special treatments



U.V. protection



Bi-colouring




Matt treatment



IR treatment

For information on resistance to chemical agents, frame the QR Code:

**POLYPIU**



LIABILITY CLAUSE: all information and technical guidance provided is given in good faith and according to the best of our knowledge. However, as we have no control over how our materials are used, we accept no responsibility for their application. The instructions do not exempt the purchaser from carrying out their own checks to ensure that the materials comply with their own needs and the current regulations. Polypiù S.r.l. reserves the right to modify its products and the content of its documentation at any time without prior notice.