


PRODUCT:

TECNOPIU'

Tecnopiù 40/8-5G

SHEET SECTION



TECHNICAL SPECIFICATIONS:

DATA	UNIT	SPECIFICATIO NS
Thickness	mm	8 ±5%
Sheet pitch	mm	1000 ±5
Rib pitch	mm	250
Rib height	mm	46 central 39 side
Sheet length	m	To measure (max recommended length: 7.00 m)
Bending	(R) m	Standard hot bending R 3.5 or 6
Compliant with the reference standard	-	UNI EN 16153:A1:2015
Colour	-	Satined clear and Opal
Structure	-	Cell with 3 parallel walls
U.V. protection	-	UV-protected on the external side
Fire Classification	-	B s1 d0
Operating temperature	°C	-40° / + 130°
Linear Thermal Expansion	mm/mm °C	6.7 x10 ⁻⁵
Resistance to chemical agents and use and maintenance	-	Refer to the catalogue for the specifications
Thermal Transmittance	W/m ² K	U= 2.90
Light transmission	%	Clear 77 ±2 Opal 67 ±2
Warranty	-	10 years - Refer to our Warranty for the terms and conditions

Special treatments



U.V. protection



Bi-colouring



Matt treatment



IR treatment

For information on resistance to chemical agents, frame the QR Code:

POLYPIU

